

**PETROPLAST
JALILVAND.CO**



**петрупдосте жалилванд
компания**

Exclusive Representative of selling shazand

Petrochemical Products in uzbekistan

TECHNICAL SPECIFICATION

Acrylonitrile Butadiene Styrene (ABS)

<i>Grade</i>	SD0150
<i>Applications</i>	General injection, Home appliances casing.

Typical Properties	Test Method	Unit	Spec.
MFI (200°C, 5kg)	ASTM D1238	gr/10min	1.8
Izod Impact Strength	ASTM D256	kJ/m ²	22
Vicat Softening Point (50N Load)	ASTM D1525	°C	98
Bulk Density	-	kg/m ³	600
Tensile Strength at Yield	ASTM D638	kgf/cm ²	450
Rockwell Hardness at 23°C	ASTM D785	R Scale	105

Central Office: Unit 5, No.10, Sepehr 4 Alley, Sepehr St., Marzdaran Blvd., Zhandarmeri Town, Tehran, Iran.

Telfax: +98 21 4428 4731-2

Mashhad Office: Shahed 50th, Shahed Blvd., Gharb Town, Mashhad, Iran.

Tel.: +985136202400-1

Uzbekistan Tel.: +998 97 404 0929

Website: www.petroplastjalilvand.com

E-mail: info@petroplastjalilvand.com