

**PETROPLAST
JALILVAND.CO**



**петрупдоте жалилванд
компания**

Exclusive Representative of selling shazand

Petrochemical Products in uzbekistan

TECHNICAL SPECIFICATION

Acetic Acid

Product Name

AA

Application

ACETIC ACID is used in the production of vinyl acetate and as esterifying agent in the production of acetate esters and Monochloroacetic acid. ACETIC ACID is also important as a reaction solvent and as a reagent in the production of rubber, plastics, acetate fibers, dyes, insecticides, photographic chemicals and textiles.

Typical Properties	Test Method	Unit	Spec.
Purity	ASTM E302	%wt	99.5 Min
Water Content	ASTM E203	%wt	0.4 Max
Formic Acid	ASTM D3546	%wt	0.15 Max
Acetaldehyde	ASTM GCL3	PPM	300 Max
Iron	ASTM D3941	PPM	1 Max
Sr. Gr (20/20°C)	ASTM D4052	-	1.0505-1.0525
Color	ASTM D1209	APHA	10 Max

Central Office: Unit 5, No.10, Sepehr 4 Alley, Sepehr St., Marzdaran Blvd., Zhandarmeri Town, Tehran, Iran.

Telfax: +98 21 4428 4731-2

Mashhad Office: Shahed 50th, Shahed Blvd., Gharb Town, Mashhad, Iran.

Tel.: +985136202400-1

Uzbekistan Tel.: +998 97 404 0929

Website: www.petroplastjalilvand.com

E-mail: info@petroplastjalilvand.com