

**PETROPLAST
JALILVAND.CO**



**петрупдосте жалилванд
компания**

Exclusive Representative of selling shazand

Petrochemical Products in uzbekistan

TECHNICAL SPECIFICATION

High Density Polyethylene - Injection Moulding (Basell Licensee)

<i>Grade</i>	HC7260
<i>Application</i>	Tick walled, highly stressed transport containers, e.g. refuse bin and fish crates, screw caps and cable clips

Typical Properties	Test Method	Unit	Spec.
MFI (2.16kg)	ISO 1133	gr/10min	4
MFI (5kg)	ISO 1133	gr/10min	11
Density	ISO 1183	gr/cm ³	0.954
Notched Impact at 23°C	ISO 179/1 eA	mJ/mm ²	5

Central Office: Unit 5, No.10, Sepehr 4 Alley, Sepehr St., Marzdaran Blvd., Zhandarmeri Town, Tehran, Iran.

Telfax: +98 21 4428 4731-2

Mashhad Office: Shahed 50th, Shahed Blvd., Gharb Town, Mashhad, Iran.

Tel.: +985136202400-1

Uzbekistan Tel.: +998 97 404 0929

Website: www.petroplastjalilvand.com

E-mail: info@petroplastjalilvand.com