

**PETROPLAST
JALILVAND.CO**



**петрупдосте жалилванд
компания**

Exclusive Representative of selling shazand

Petrochemical Products in uzbekistan

TECHNICAL SPECIFICATION

High Density Polyethylene – Extrusion – Blow Moulding

Grade	HH4765
Application	For hollow articles where high stress cracking resistance is not demanded, such as bottles and containers up to 10 liters, e.g. for fabric softeners.

Typical Properties	Test Method	Unit	Spec.
MFI (190°C, 5kg)	ISO 1133	gr/10min	1.5
MFI (190°C, 21.6kg)	ISO 1133	gr/10min	27
FRR (21.6/5)	-	-	18
Density	ISO 1183	gr/cm ³	0.959
Notched Impact (23°C)	ISO 179/1 eA	mJ/mm ²	7

Central Office: Unit 5, No.10, Sepehr 4 Alley, Sepehr St., Marzdaran Blvd., Zhandarmeri Town, Tehran, Iran.

Telfax: +98 21 4428 4731-2

Mashhad Office: Shahed 50th, Shahed Blvd., Gharb Town, Mashhad, Iran.

Tel.: +985136202400-1

Uzbekistan Tel.: +998 97 404 0929

Website: www.petroplastjalilvand.com

E-mail: info@petroplastjalilvand.com