

**PETROPLAST
JALILVAND.CO**



**петрупдоте жалилванд
компания**

Exclusive Representative of selling shazand

Petrochemical Products in uzbekistan

TECHNICAL SPECIFICATION

Linear Low Density Polyethylene - Blown Film (Innovene licensee)

Grade	LL0209AA
Application	Liner bags, builders reel, co-extrusion, shrink silage, green house and mulch film

Typical Properties	Test Method	Unit	Spec.
MFI (190°C, 2.16kg)	D1238/L	gr/10min	0.9
Density	D2839	gr/ml	0.920
Vicat Softening Point, 10N	D1525	°C	100
Tensile Strength at Yield, MD/TD	D638	MPa	10.5/11
Elongation at Break, MD/TD	D638	%	620/840
Tensile Strength at Break, MD/TD	D688	MPa	41/32
Tear Strength, MD/TD	D1922	gr/25mic	145/370
Impact Strength, Dart	D1709	gr	150
Haze	D1003	%	10
Gloss (45°)	D2457	Rating	56

Central Office: Unit 5, No.10, Sepehr 4 Alley, Sepehr St., Marzdaran Blvd., Zhandarmeri Town, Tehran, Iran.

Telfax: +98 21 4428 4731-2

Mashhad Office: Shahed 50th, Shahed Blvd., Gharb Town, Mashhad, Iran.

Tel.: +985136202400-1

Uzbekistan Tel.: +998 97 404 0929

Website: www.petroplastjalilvand.com

E-mail: info@petroplastjalilvand.com