

**PETROPLAST  
JALILVAND.CO**



**петропдосте жалилванд  
компания**

Exclusive Representative of selling shazand

Petrochemical Products in uzbekistan

## TECHNICAL SPECIFICATION

*Linear Low Density Polyethylene - Blown Film (Innovene licensee)*

<b>Grade</b>	LL0209KJ
<b>Application</b>	Liner bags, deep freeze film, garment wrap, refuse and Heavy duty sacks

<b>Typical Properties</b>	<b>Test Method</b>	<b>Unit</b>	<b>Spec.</b>
MFI (190°C, 2.16kg)	D1238/L	gr/10min	0.9
Density	D2839	gr/ml	0.920
Vicat Softening Point, 10N	D1525	°C	100
Tensile Strength at Yield, MD/TD	D638	MPa	10.5/11
Elongation at Break, MD/TD	D638	%	620/840
Tensile Strength at Break, MD/TD	D638	MPa	41/32
Tear Strength, MD/TD	D1922	gr/25mic	145/370
Impact Strength, Dart	D1709	gr	150
Haze	D1003	%	10
Gloss (45°)	D2457	Rating	56

**Central Office:** Unit 5, No.10, Sepehr 4 Alley, Sepehr St., Marzdaran Blvd., Zhandarmeri Town, Tehran, Iran.

**Telfax:** +98 21 4428 4731-2

**Mashhad Office:** Shahed 50<sup>th</sup>, Shahed Blvd., Gharb Town, Mashhad, Iran.

**Tel.:** +985136202400-1

**Uzbekistan Tel.:** +998 97 404 0929

**Website:** [www.petroplastjalilvand.com](http://www.petroplastjalilvand.com)

**E-mail:** [info@petroplastjalilvand.com](mailto:info@petroplastjalilvand.com)