

**PETROPLAST
JALILVAND.CO**



**петрупдоте жалилванд
компания**

Exclusive Representative of selling shazand

Petrochemical Products in uzbekistan

TECHNICAL SPECIFICATION

Polypropylene - Homopolymer - Bioriented Film (BOPP Film)

<i>Grade</i>	S38FT
<i>Properties</i>	Excellent process ability on tubular lines.
<i>Application</i>	Adhesive tapes. Packaging in general.

Typical Properties	Test Method	Unit	Spec.
MFI (230°C, 2.16kg)	D1238/L	gr/10min	1.8
Flexural Modulus	D790	MPa	1450
Tensile Strength at Yield	D638	MPa	36
Elongation at Break	D638	%	12
Vicat Softening Point, 10N	D1525	°C	152
Notched Izod Impact at 23°C	D256	J/m	60
HDT (0.46N/mm ²)	D648	°C	94
Oven Aging at 150°C	D3012	Hours	360

Central Office: Unit 5, No.10, Sepehr 4 Alley, Sepehr St., Marzdaran Blvd., Zhandarmeri Town, Tehran, Iran.

Telfax: +98 21 4428 4731-2

Mashhad Office: Shahed 50th, Shahed Blvd., Gharb Town, Mashhad, Iran.

Tel.: +985136202400-1

Uzbekistan Tel.: +998 97 404 0929

Website: www.petroplastjalilvand.com

E-mail: info@petroplastjalilvand.com