

**PETROPLAST
JALILVAND.CO**



петрупдоте жалилванд
компания

Exclusive Representative of selling shazand

Petrochemical Products in uzbekistan

TECHNICAL SPECIFICATION

Expandable Polystyrene (EPS)

<i>Grade</i>	FC422
<i>Application</i>	Shape molding, High density block.
<i>Alarm</i>	This product is not fire-retardant, so not suitable for building applications.

Typical Properties	Test Method	Unit	Spec.
Bead Size	SUNPOR 7.2.5 (Min 90% By WT)	mm	(0.5-0.7)(>90%wt)
K-Value	SUNPOR 7.2.4	-	55
Pentane Content	SUNPOR 7.2.2	%wt	>5
Expanded Density	SUNPOR 7.2.6	kg/m ³	20-30
Residual Monomer	SUNPOR 7.2.1	PPM	500

Central Office: Unit 5, No.10, Sepehr 4 Alley, Sepehr St., Marzdaran Blvd., Zhandarmeri Town, Tehran, Iran.

Telfax: +98 21 4428 4731-2

Mashhad Office: Shahed 50th, Shahed Blvd., Gharb Town, Mashhad, Iran.

Tel.: +985136202400-1

Uzbekistan Tel.: +998 97 404 0929

Website: www.petroplastjalilvand.com

E-mail: info@petroplastjalilvand.com