

**PETROPLAST  
JALILVAND.CO**



**петрупдосте жалилванд  
компания**

Exclusive Representative of selling shazand

Petrochemical Products in uzbekistan

## TECHNICAL SPECIFICATION

### *General Purpose Polystyrene (GPPS)*

<i>Grade</i>	GPPS1240
<i>Application</i>	Ultra HMW for special extrusion, Impact dilution, Special injection molding.

<b>Typical Properties</b>	<b>Test Method</b>	<b>Unit</b>	<b>Spec.</b>
MFI (200°C, 5kg)	ASTM D1238	gr/10min	2.5
Styrene Residual Monomer	CLG LABPSG004 (ATOFINA Test Method)	PPM	<500
Vicat Softening Point (50°C/hr, 1kg)	ASTM D1525	°C	96
Tensile Strength at Break	ASTM D638	MPa	53
Elongation at Break	ASTM D638	%	3
Tensile Modulus	ASTM D638	MPa	4300

**Central Office:** Unit 5, No.10, Sepehr 4 Alley, Sepehr St., Marzdaran Blvd., Zhandarmeri Town, Tehran, Iran.

**Telfax:** +98 21 4428 4731-2

**Mashhad Office:** Shahed 50<sup>th</sup>, Shahed Blvd., Gharb Town, Mashhad, Iran.

**Tel.:** +985136202400-1

**Uzbekistan Tel.:** +998 97 404 0929

**Website:** [www.petroplastjalilvand.com](http://www.petroplastjalilvand.com)

**E-mail:** [info@petroplastjalilvand.com](mailto:info@petroplastjalilvand.com)