

**PETROPLAST
JALILVAND.CO**



**петрупдосте жалилванд
компания**

Exclusive Representative of selling shazand

Petrochemical Products in uzbekistan

TECHNICAL SPECIFICATION

High Impact Polystyrene (HIPS)

<i>Grade</i>	HIPS7240WB
<i>Application</i>	Industrial parts, Packaging containers, Egg box.

Typical Properties	Test Method	Unit	Spec.
MFI (200°C, 5kg)	ASTM D1238	gr/10min	4.5
Styrene Residual Monomer	CLG LABPSG004 (ATOFINA Test Method)	PPM	<500
Vicat Softening Point (50°C/hr, 1kg)	ASTM D1525	°C	97
Rockwell Hardness	ASTM D1525	-	Scale/R65
Tensile Strength at Yield	ASTM D638	MPa	23
Tensile Strength at Break	ASTM D638	MPa	21
Elongation at Break	ASTM D638	%	60
Tensile Modulus	ASTM D638	MPa	1950
Izod Impact	ASTM D256	kJ/m ²	11

Central Office: Unit 5, No.10, Sepehr 4 Alley, Sepehr St., Marzdaran Blvd., Zhandarmeri Town, Tehran, Iran.

Telfax: +98 21 4428 4731-2

Mashhad Office: Shahed 50th, Shahed Blvd., Gharb Town, Mashhad, Iran.

Tel.: +985136202400-1

Uzbekistan Tel.: +998 97 404 0929

Website: www.petroplastjalilvand.com

E-mail: info@petroplastjalilvand.com